



Product Name	Solar Street Light					
Model No.	GTL-WE90w					
Power	90W					
Product size	62*24*5.5					
cantoon size	64.5*50.5*25.5CM					
QTY/CTN	8pcs					
N.W/CTN	21KG					
G.W/CTN	22.05KG					
20GP container	2376pcs					
40HQ container	5784pcs					
Reflector material	Electroplated PC					
Lamp material	PC+ABS					
Lens	High light effect PC					
Bracket material	Iron					
Beam angle	60°					
IP Rate	IP66					
screw	Stainless steel					
Test item	charger test	☒		aging test	☒	
	insulation test	☒		discharging	☒	
	leakage test	☒		package test	☒	
	IP rating test	☒		sunlight test	☒	
Battery display	light control+ Radar induction+ remote control					
CCT	8000K±8500K					
CRI	>70					
Lumen	550LM	770LM	1080LM	1380LM	1850LM	

Light effect	>110LM/W
Life time	50000 hurs
Charge time	4-6 hours
Working time	More than 12 hours everyday
Warranty	2 Years
Application	Courtyards, streets, parks, country roads
Working model	always bright more than 48hours (Product data are all factory laboratory data. If there is any deviation, the actual products shall prevail) Remote control:3hours timer/5hours timer/8hours timer/ Increase brightness/Reduce brightness induction (100% bright when people come and 10% bright when people walk)
Working Temperature	-30℃~55℃
Charger model	solar charger
Operating Temperature	-20℃~55℃
Storage Temperature	-30℃~55℃
Introduction	1. High temperature resistance, anti-aging, good sealing of lamp body, dustproof. 2. The surface of the reflective cover is chromium plated, which is closely fitted with the light source and has high reflective efficiency. 3. The use of high efficiency lithium battery storage capacity, long discharge time, longer life 4. The SMD patch LED with high quality chip packaging ensures high efficiency, low consumption and stability. 5. Beam Angle 60, using high light transmittance reflective material, so that the whole lighting effect is higher, higher luminous uniformity. 6. Solar panel: Polycrystalline silicon solar panel, good performance for rainy days.  